


 **PIONEER**

Service Manual

**CIRCUIT & MECHANISM
DESCRIPTIONS**



The photo shows the model KEH-9300 SDK/WG.

**ORDER NO.
CRT-398-0**

CASSETTE CAR STEREO WITH FM/MW/LW ELECTRIC TUNER

KEH-9300SDK WG

KEH-9300 EW

CASSETTE CAR STEREO WITH FM/AM ELECTRIC TUNER

KEH-9000 ES

- For the repair and adjustments, please refer to the service manual (CRT-387).
- 'Dolby' and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.
- Noise Reduction System manufactured under license from Dolby Laboratories Licensing Corporation.

CONTENTS

1. SPECIFICATIONS.....	1
2. OPERATION.....	1
3. CONNECTION.....	7
4. CIRCUIT DESCRIPTION.....	9

PIONEER ELECTRONIC CORPORATION 4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153, Japan
PIONEER ELECTRONICS (USA) INC. P.O. Box 1760, Long Beach, California 90801 U.S.A.
PIONEER ELECTRONIC (EUROPE) N.V. Keetberglaan 1, 2740 Beveren, Belgium
PIONEER ELECTRONICS AUSTRALIA PTY. LTD. 178-184 Boundary Road, Braeside, Victoria 3195, Australia

EK © JAN. 1984 Printed in Japan

1. SPECIFICATIONS

General (KEH-9300SDK)

Power source DC14.4V (10.8 ~ 15.6V allowable)
 Grounding system Negative type
 Max. current consumption 5A
 Dimensions (chassis) 180(W)×50(H)×160(D) mm
 (front face) 184(W)×56(H)×16(D) mm
 Weight 2.1 kg

General (KEH-9300, 9000)

Power source DC 14.4V (10.8 ~ 15.6V allowable)
 Grounding system Negative type
 Max. current consumption 5A
 Dimensions (chassis) 180(W)×50(H)×150(D) mm
 (front face) 184(W)×56(H)×16(D) mm
 Weight 2 kg

Amplifier

Maximum power output
 (2 speaker) 20W + 20W
 (4 speaker) 6.5W + 6.5W
 Continuous power output
 (2 speaker) 13W + 13W (1% dist. at 1 kHz)
 (4 speaker) 4.5W + 4.5W (1% dist. at 1 kHz)
 Load impedance
 (2 speaker) 4Ω (4 ~ 8Ω allowable)
 (4 speaker) 4Ω (2 ~ 8Ω allowable)
 Graphic equalizer
 (60, 250, 1k, 3.5k, 10 kHz) ±10 dB

Tape player

Tape Compact cassette tape (C-30 ~ C-90)
 Tape speed 4.76 cm/sec.
 (+ 0.14 cm/sec., -0.05 cm/sec.)
 Fast forward/rewind time Approx. 100 sec. for C-60
 Wow & flutter 0.13% (WRMS)

Frequency response Metal: 50 ~ 16,000 Hz (±3 dB)
 Normal: 50 ~ 12,000 Hz (±3 dB)
 Stereo separation 45 dB
 Signal-to-noise ratio Dolby NR IN: 60 dB (IEC-A network)
 Dolby NR OUT: 52 dB (IEC-A network)

FM tuner (KEH-9300SDK)

Frequency range 87.5 ~ 108 MHz
 Usable sensitivity 13.2 dBf (1.8 μV/150Ω, mono)
 50 dB quieting sensitivity 18.2 dBf (3 μV/150Ω, mono)
 Signal-to-noise ratio 70 dB (IEC-A network)
 Distortion 0.3% (at 65 dBf, 1 kHz, stereo)
 Frequency response 50 ~ 12,000 Hz (±3 dB)
 Stereo separation 40 dB (at 65 dBf, 1 kHz)

FM tuner (KEH-9300, 9000)

Frequency range 87.5 ~ 108 MHz
 Usable sensitivity 12 dBf (1.1 μV/75Ω, mono)
 50 dB quieting sensitivity 17 dBf (1.9 μV/75Ω, mono)
 Signal-to-noise ratio 70 dB (IEC-A network)
 Distortion 0.3% (at 65 dBf, 1 kHz, stereo)
 Frequency response 50 ~ 12,000 Hz (±3 dB)
 Stereo separation 40 dB (at 65 dBf, 1 kHz)

MW tuner (AM tuner)

Frequency range 531 ~ 1,602 kHz
 Usable sensitivity 18 μV (25 dB) (S/N: 20 dB)
 Selectivity 30 dB (±9 kHz)

LW tuner (KEH-9300SDK, 9300)


Frequency range 153 ~ 281 kHz
 Usable sensitivity 30 μV (30 dB) (S/N: 20 dB)
 Selectivity 30 dB (±9 kHz)

Note:

Specifications and the design are subject to possible modification without notice due to improvements.

2. OPERATION

• KEH-9300SDK



To Listen to a Tape

1. Insert the cassette tape into the Cassette Insertion Slot ④ until it is locked in position with the exposed piece of tape on the right. (The unit will automatically switch to the tape mode when a cassette is inserted while the radio is on.) (Fig. 1)
2. Adjust Volume ②, Balance ②, and Fader ① Controls. Pull out the Balance Control Knob ② and rotate to adjust balance.
3. Depress the Direction Change Button ⑦ to switch over from the side of the tape you are listening to now to the other side during play.
4. To fast forward the tape, depress the Fast Forward/Rewind Button ⑥ pointing in the same direction as the Direction Indicator until it locks into position. To rewind the tape, depress the Fast Forward/Rewind Button pointing in the opposite direction to the Direction Indicator until it locks into position. To release the fast forward or rewind mode, simply depress the other button lightly. (Fig. 2)
To change from fast forward to rewind or vice versa, depress the other button directly until it locks and this will change the traveling direction of the tape. When the tape has been fully wound up in the fast forward mode, the fast forward mode is released and play begins automatically from the first program on the other side of the tape. When the tape has been fully wound up in the rewind mode, the rewind mode is released and play begins automatically from the first program on the side you have been listening to.
5. To stop tape play or replace the cassette, fully depress both Fast Forward/Rewind Buttons ⑥ at the same time. (Fig. 3)

Note:

Do not try to eject the cassette immediately after insertion, as it will cause malfunction. Wait a few seconds.




Fig. 1



Fig. 2




Fig. 3

Fader Control ①

Adjusts front-to-rear balance of four speaker system. (Fig. 4)

Equalizer Control Levers ③

By sliding these levers up and down, the desired sound can be created to match the music. (Fig. 5)

Musical instruments and vocals each possess their respective individual frequency ranges. The graphic equalizer divides these music sources into several frequency bands and since the level of each of these frequency bands can be increased or decreased, fine adjustments can be made which cannot be performed using ordinary tone controls. (Fig. 6)

Dolby NR Switch ⑧

When listening to a tape recorded with Dolby NR, press this switch. The Dolby NR Indicator will light. (Fig. 7)

Tape Select Button ⑨

Set this button to the position that corresponds to the type of tape you are using. If the button is pressed, the Metal Indicator will illuminate. (Fig. 8)




Fig. 4




Fig. 5




Fig. 6






Fig. 7

Fig. 8

• KEH-9300



• KEH-9000



To Listen to the Radio (KEH-9300SDK, 9300)

1. When the Radio Power Switch ② is pushed on, the radio frequency will appear on the Digital Display ⑤. (Fig. 9)
2. Press Band Select Button ③ to select the desired band and Digital Display ⑤ will illuminate to indicate the band.
3. Tune in desired station.

There are several methods of finding the radio station you wish to listen to.

Manual Tuning


Press Manual/Seek Select Button ⑫ to select Manual Tuning. (Digital Display ⑤ indicates nothing during Manual Tuning but SEEK illuminates during Seek Tuning.) Press the right or left side of Tuning Button ⑪ to set the desired station. (Fig. 10)

FM Band

Each time the \triangleright Tuning Button ⑪ is pressed, the frequency increases 25kHz. If you continue to press the button without releasing it, the frequency will continuously increase in 25kHz increments. (Fig. 11)

Each time the \triangleleft Tuning Button ⑪ is pressed, the frequency decreases 25kHz. If you continue to press the button without releasing it, the frequency will continuously decrease in 25kHz increments. (Fig. 12)

When a strong FM Stereo station is received, the FM Stereo Indicator will illuminate.



Indicates the frequency tuned in.

Fig. 9






Fig. 10



This portion of the frequency indicator goes from 25 to 50 to 75.

Fig. 11



This portion of the frequency indicator goes from 75 to 50 to 25.

Fig. 12

MW Band

Each time the \triangleright Tuning Button ⑪ is pressed, the frequency increases 9kHz. If you continue to press the button without releasing it, the frequency will continuously increase in 9kHz increments.

Each time the \triangleleft Tuning Button ⑪ is pressed, the frequency decreases 9kHz. If you continue to press the button without releasing it, the frequency will continuously decrease in 9kHz increments.

LW Band

Each time the \triangleright Tuning Button ⑪ is pressed, the frequency increases 1kHz. If you continue to press the button without releasing it, the frequency will continuously increase in 1kHz increments.

Each time the \triangleleft Tuning Button ⑪ is pressed, the frequency decreases 1kHz. If you continue to press the button without releasing it, the frequency will continuously decrease in 1kHz increments.

Seek Tuning

Press Manual/Seek Button ⑫ to select Seek Tuning. (At this time, SEEK in the Digital Display ⑤ illuminates.)

If the \triangleright Tuning Button ⑪ is pressed, the next higher, clearly receivable station will be tuned automatically.

If the \triangleleft Tuning Button ⑪ is pressed, the next lower, clearly receivable station will be tuned automatically.

Remote Control Seek Switch:

Remote control seek tuning is possible by connecting the accessory Remote Control Seek Switch.

Press the UP side of this switch and the next higher clearly receivable station will be tuned automatically. Press the DOWN side and the next lower, clearly receivable station will be tuned automatically.

Press the Manual/Seek Select Button ⑫ and Manual Tuning is possible at the same time.

FM Band

Each time a Tuning Button ⑪ is pressed, the frequency increases or decreases to the next clearly receivable station in 5kHz increments.

For fine frequency adjustments, return the Manual/Seek Select Button to the Manual position and adjust the frequency using the Tuning Button.

MW Band

Each time a Tuning Button ⑪ is pressed, the frequency increases or decreases to the next clearly receivable station in 9kHz increments.

LW Band

Each time a Tuning Button ⑪ is pressed, the frequency increases or decreases to the next clearly receivable station in 9kHz increments. Since the LW Band frequency range of this unit is 153kHz to 281kHz, stations selectable using Seek Tuning are 155kHz, 164kHz, 173kHz, 182kHz... 272kHz and 281kHz. (During manual tuning, the frequency is changed in increments of 9kHz. When the upper end of the frequency band, 281kHz, is reached during manual tuning, the tuning automatically starts from the lower end, 155kHz, again.)

To tune a station on another frequency, return the Manual/Seek Select Button ⑫ to the Manual position and tune the station in 1kHz increments using the Tuning Button.

To Listen to the Radio (KEH-9000)

1. When the Radio Power Switch ② is pushed on, the radio frequency will appear on the Digital Display ⑤. (Fig. 9)
2. Press Band Select Button ③ to select the desired band and Digital Display ⑤ will illuminate to indicate the band.
3. Tune in desired station.
There are several methods of finding the radio station you wish to listen to.

Manual Tuning

Press Manual/Seek Select Button ⑫ to select Manual Tuning. (Digital Display ⑤ indicates nothing during Manual Tuning but SEEK illuminates during Seek Tuning.) Press the right or left side of Tuning Button ⑪ to set the desired station. (Fig. 10)

FM Band

Each time the \triangleright Tuning Button ⑪ is pressed, the frequency increases 25kHz. If you continue to press the button without releasing it, the frequency will continuously increase in 25kHz increments. (Fig. 11)

Each time the \triangleleft Tuning Button ⑪ is pressed, the frequency decreases 25kHz. If you continue to press the button without releasing it, the frequency will continuously decrease in 25kHz increments. (Fig. 12)

When a strong FM Stereo station is received, the FM Stereo Indicator will illuminate.




Fig. 9




Fig. 10




Fig. 11




Fig. 12

AM Band

Each time the \triangleright Tuning Button ⑪ is pressed, the frequency increases 9kHz. If you continue to press the button without releasing it, the frequency will continuously increase in 9kHz increments.

Each time the \triangleleft Tuning Button ⑪ is pressed, the frequency decreases 9kHz. If you continue to press the button without releasing it, the frequency will continuously decrease in 9kHz increments.

Seek Tuning

Press Manual/Seek Button ⑫ to select Seek Tuning. (At this time, SEEK in the Digital Display ⑤ illuminates).

If the \triangleright Tuning Button ⑪ is pressed, the next higher, clearly receivable station will be tuned automatically.

If the \triangleleft Tuning Button ⑪ is pressed, the next lower, clearly receivable station will be tuned automatically.

Remote Control Seek Switch:

Remote control seek tuning is possible by connecting the accessory Remote Control Seek Switch.

Press the UP side of this switch and the next higher clearly receivable station will be tuned automatically. Press the DOWN side and the next lower, clearly receivable station will be tuned automatically.

Press the Manual/Seek Select Button ⑫ and Manual Tuning is possible at the same time.

FM Band

Each time a Tuning Button ⑪ is pressed, the frequency increases or decreases to the next clearly receivable station in 50kHz increments.

For fine frequency adjustments, return the Manual/Seek Select Button to the Manual position and adjust the frequency using the Tuning Button.

AM Band

Each time a Tuning Button ⑪ is pressed, the frequency increases or decreases to the next clearly receivable station in 9kHz increments.

Programming Stations (KEH-9300SDK, 9300)

You can preset a total of 18 stations (six FM, six MW and six LW) using the six feather-touch Preset Buttons. One button can store one station each for FM, MW and LW.

1. Press Band Select Button **13** and Digital Display **5** will display FM.
 2. Tune to the desired station using Manual Tuning or Seek Tuning.
 3. Press the Memory Button **15** and the Memory Indicator (ME) will illuminate on the Digital Display **5**. Press one of the Preset Buttons **14** during the 5-second period that the Memory Indicator is illuminated. At this time the number of the preset button will illuminate. (Fig. 13)
 4. One station has now been memorized for one of the Preset Buttons. Repeat steps (2) and (3) for each of the remaining five Preset Buttons.
 5. Switch Band Select Button **13** to MW and then LW, and repeat steps (2), (3) and (4).
- Preset Button Indicator PRE is not illuminated for Manual Tuning or Seek Tuning. (Number display is unchanged.)

Local Station Seek Switch **16**

At night when FM/MW/LW station broadcast signals are too strong, press this switch when unwanted stations often come in when using Seek Tuning. (At this time, LOC in the Digital Display **5** illuminates). Tuner sensitivity is not affected after a station is locked on.

Press the switch again and LOC display goes out.

FM Auto/Mono Select Button **10**

This button will only function with an FM broadcast. (Fig. 14)

FM Auto: In most cases, this button should be left in this position. The following functions are automatically activated according to the strength of the incoming FM signal:

- Hi-Fi stereo quality is reproduced with a strong FM stereo signal.
- Reception is automatically controlled (stereo separation is gradually narrowed and high frequency is slightly attenuated) to reduce background noise as the incoming signal weakens. Eventually, reception is switched to monaural.

FM Mono: For monaural reception, regardless of the strength of the incoming FM signal or whether it is stereo or monaural.




Fig. 13



Fig. 14

Programming Stations (KEH-9000)

You can preset a total of 18 stations (six FM1, six FM2 and six AM) using the six feather-touch Press Buttons. One button can store one station each for FM1, FM2 and AM. To listen to an FM broadcast, set to either FM1 or FM2. Both FM1 and FM2 are in a frequency band between 87.5 and 108MHz.

1. Press Band Select Button **13** and Digital Display **5** will display FM1.
 2. Tune to the desired station using Manual Tuning or Seek Tuning.
 3. Press the Memory Button **15** and the Memory Indicator (ME) will illuminate on the Digital Display **5**. Press one of the Preset Buttons **14** during the 5-second period that the Memory Indicator is illuminated. At this time the number of the Preset Button will illuminate. (Fig. 13)
 4. One station has now been memorized for one of the Preset Buttons. Repeat steps (2) and (3) for each of the remaining five Preset Buttons.
 5. Switch Band Select Button **13** to FM2 and then AM, and repeat steps (2), (3) and (4).
- Preset Button Indicator PRE is not illuminated for Manual Tuning or Seek Tuning. (Number display is unchanged.)

Local Station Seek Switch **16**

At night when FM/AM station broadcast signals are too strong, press this switch when unwanted stations often come in when using Seek Tuning. (At this time, LOC in the Digital Display **5** illuminates). Tuner sensitivity is not affected after a station is locked on.

Press the switch again and LOC display goes out.

FM Auto/Mono Select Button **10**

This button will only function with an FM broadcast. (Fig. 14)

FM Auto: In most cases, this button should be left in this position. The following functions are automatically activated according to the strength of the incoming FM signal:

- Hi-Fi stereo quality is reproduced with a strong FM stereo signal.
- Reception is automatically controlled (stereo separation is gradually narrowed and high frequency is slightly attenuated) to reduce background noise as the incoming signal weakens. Eventually, reception is switched to monaural.

FM Mono: For monaural reception, regardless of the strength of the incoming FM signal or whether it is stereo or monaural.




Fig. 13




Fig. 14

To Listen to Traffic Information (KEH-9300SDK)

1. Push Radio Power Switch ②. Press Band Select Button ⑩ and Digital Display ⑤ will illuminate to indicate FM. (Fig. 15)
2. Press SDK Switch ⑦ and Digital Display will illuminate. Press Tuning Button ① to receive traffic information broadcasts for the area through which you are driving. The SK indicator will illuminate when a signal is received.
3. The volume will become louder when a traffic information announcement is received during a broadcast. Volume cannot be lowered by turning the Volume Control ② to the left.
4. As the traffic information broadcast signal weakens, and you reach an area where the signal cannot be picked up at all, the SK Indicator will go out, indicating that traffic information can no longer be monitored. If this situation persists for more than 30 seconds, an alarm will beep to alert the driver. In such a case, either receive another traffic information broadcast station, turn the SDK Switch ⑦ off, or switch to the MW or LW band by pushing the Band Select Button ⑩.




Fig. 15

Note:


Keep the SDK Switch off to listen to FM broadcast that is not a traffic information broadcast.

- Traffic information can be monitored in tape playback, fast forward and rewind modes.
- To listen to tape only, turn SDK Switch or Radio Power Switch off. Press Band Select Button to select an MW or LW station.


3. CONNECTION

3.1 KEH-9300SDK, 9000

• Four-speaker System




• Two-speaker High-power System



- Set the speaker mode selector switch to 2SP when using the 2-speaker high-power system.
- Speakers for the 2-speaker high power system have maximum power output of over 20W, so be sure the impedance is 4 to 8Ω. Be aware of the fact that using a speaker other than the one specified can cause the speaker to be damaged.
- A special BPTL circuit is used so be sure that you do not connect the speaker directly to ground nor join the left and right speaker (-) leads.

3.2 KEH-9300


• Four-speaker System



This unit can be operated with either a four-speaker system or a two speaker high-power system. Refer to connection diagram to find out how to connect the speakers.

- Set the speaker mode selector switch to 4SP when using the 4-speaker system.
- Whenever replacing a fuse be sure to replace with one of the same capacity.

• Two-speaker High-power System



4. CIRCUIT DESCRIPTION

• Level Diagram




Fig. 1

• Block Diagram (KEH-9300SDK)




Fig. 2

• Block Diagram (KEH-9300)





Fig - 3

• Block Diagram (KEH-9000)



• Operation of FM Section




Fig. 5

ARC Mark V

The high-cut and separation, which were controlled by the input signal strength level in the ARC Mark III, can also be controlled by the noise level in the ARC Mark V. Therefore noise in strong signal areas, impossible to suppress before, can now be suppressed adequately.

Noise Detector Circuit

Co-using the PNS HIGH PASS FILTER, this operates by detecting the components above 100 kHz in the wave detector output. The HPF output is amplified to a sufficient level, rectified, phase reversed and then DC converted.

Input Level 35 dB μ V Switch

The noise level ceases to control the high-cut and separation when the input level drops below 35 dB μ V, and control of these is carried out entirely by the input signal strength level. This is the same as in the Mark III. This function operates in this manner because the noise level control will always output a signal when the signal strength is below 35 dB μ V, and signal strength control is sufficient for medium-weak input signal areas.

1. Front end section




Fig. 6

The RF signal from the antenna passes through an attenuator constructed as a band-pass filter and is sent to the pi-shaped matching circuit, where high-end spurious response is improved. The signal then goes to the next stage, the RF amp. The RF amp employs a MOS FET capable of handling a wide dynamic range. The output from the RF amp passes through a parallel resonance circuit, is converted to a balanced signal from an unbalanced by a balun circuit and then

goes to the mixer stage. This is a J-FET single balance type mixer which can accommodate a wide dynamic range. One of the IF signals from the mixer passes through the IF amp and ceramic filters. Another IF signal goes to the AGC amp. This AGC amp can operate even in the presence of interference signals. The AGC amp output is fed back to the RF attenuator circuit, forming a wide loop AGC. The AGC circuit operates at antenna input levels above 65 \pm 5 dB.

2. IF detector section

A single-tuning quadrature detection is performed by IC PA0013 using IF amp and T201 to obtain an audio frequency output.

3. PNS section

This is a pulse noise canceller using IC PA0014 and CR composite part CR201 which comprises filters.

4. Multiplexer section

Stereo multiplexing is performed by IC PA0015. This IC does not operate the stereo circuit in the absence of current flowing through the stereo indicator terminal (pin 3).

5. Muting of weak incoming signals

IC PA0013 develops a DC voltage at pin 6 when the input is weak or detuned. When this voltage is applied to pin 5 through the filter consisting of capacitors and resistors, the attenuator goes into operation. The on/off (AUTO/MONO) of this weak input signal muting is controlled.

The stop signal for the seek operation uses a voltage developed at pin 6. (During broadcast reception, the voltage is at 0V).

6. Local station seeking

While seeking strong signal stations, the gain of the front end is decreased by making the voltage at AGC terminal in the front end 4.5V by Q205.

• Operation of AM Section

IC HA12434 used in this unit is designed for electronic tuning and provided with the output circuit of the stop signals for seeking and VCO buffer. Its feature includes a wide-band AGC.

1. RF amplifier section

This section performs a single-tuning 2-stage RF amplification. The first stage is a narrow-band amplifier section consisting of Q251 and its load, i.e., resonance circuit (inductance of T253, and capacitance of varicap diode D255-1, C291). The second stage is a section consisting of RF amplifier 1 inside the IC and its load, or resonance circuit (inductance of T255, and capacitance of D255-2, C292). Pin 15 is not only a terminal lead to which the load of RF amp 1 is connected, but also an input terminal pin of the mixer input.

2. VCO section

The VCO (voltage-controlled oscillator) oscillates at its resonant frequency by the feedback circuit from pin 12 to pin 13 and the resonant circuit connected to pin 13. The resonant frequency is determined by the inductance of T257 and the composite capacitance of C_A , C_B , and D255-2.

C_A is a padding capacitor connected in series with capacitance-varying varicap diode D255-3, and C_B is a capacitor connected in parallel with varicap diode depending on its grade. All this contributes to better tracking with the RF stage.

7. Separation control, high frequency control.

Pin 17 of IC203 (PA0015) functions as the separation control (SNC) pin, and pins 18 and 19 function as the high-cut control (HCC) pins. SNC and HCC are controlled by the control voltage from pin 17 of IC201 (PA0013). The control voltage can be varied by adjusting semi-fixed volume VR201, connected to pin 20 of IC201. SNC and HCC are controlled by the input signal strength level. However, these are also controlled by the noise detector level from IC202 (PA0014, PNS), unless the input signal strength is below 35 dB μ V. The noise detector output from pin 7 of CR201 is input to pin 16 of IC201. The noise detector control of the high-cut and separation will switch on above 35 dB μ V.

8. Mono/stereo

When the Mono switch is turned on, pin 6 of IC203 (PA0015) will be grounded, the stereo indicator will go out, and the output will switch to monaural. Pin 5 (MUTE DRIVE PIN) of IC201 (PA0013) will also be grounded, disengaging the level mute. Only for model KEH-9300SDK, pin 5 of IC201 will be grounded through Q315, disengaging the level mute. Q315 will go off when the SDK switch is turned on. Thus the level mute will not be disengaged.

3. Mixer section

The VCO output frequency from the VCO section and the input signal from RF amp 1 are mixed together at the mixer section to produce the IF component (450 kHz).

4. IF section

The intermediate frequency section consists of the IF filter (450 kHz) by T259 and CF251, the IF amp 1 and the IF filter by T260. Pin 8 is not only a load connecting terminal of the IF amp but also an input terminal of detector circuit 1.

5. Detector section

Pin 8 is connected to the detector and provides an output to pin 5, audio output. This output contains both audio frequency component (AC) and DC component.

6. AGC section (AGC by the reception frequency)

The DC component of the detector output at pin 5 is detected by AGC amp 1 at pin 1 by passing it through the filter consisting of R273 and C285. The AGC starts operating at an input level close to the maximum sensitivity. The output of AGC amp 1 is connected to AGC amp 2 and controls the gain of RF amp 1.

The AGC voltage is developed at pin 3 through AGC amp 3, and current flows through D251 and D252, lowering the impedance. As a result, attenuation is effected. When Q253 turns on and the load impedance of the drain of Q251 is lowered, attenuation is effected. These attenuations due to the decrease in impedance enable AGC operation.

tion. The input level to develop a voltage at pin 3 is about 55 dB μ V during reception of MW 999 kHz.

Thanks to the AGC operation mentioned above, the output variation characteristics against input variation are broader than the conventional AM characteristics.

7. AGC section (wide-band AGC)

The wide-band AGC is to control the gain of the RF amplifier section when the input RF level at pin 16 is high. This is intended to prevent interference due to the saturations of RF amp Q251, RF amp 1 in the IC, etc. Caused by a large input other than the reception frequency.

Operation is as follows: A DC voltage corresponding to the level of the input RF is developed at pin 2 by amplifying and detecting the RF signal from pin 16 by RF amp 2 and detector 3 respectively. This is delayed by the time constant of C284 and the gain of this portion is determined by R270. By applying this DC voltage to AGC amp 2, the AGC at RF amp 1 and AGC at Q253, D251 and D252 are effected.

8. Stop signal

The stop signal for seek operation is produced by extracting the IF signal from the secondary winding of T8 and adjusting its level by R287, R286 and R285. This signal is connected via 450 kHz filter CF252 from pin 7 to IF amp 2 to detector 2. This output appears at pin 6 and becomes 0V during reception.

9. Local station/distant station seek

During local station seek, Q252 turns on, whereby C253 is grounded. The impedance of C253 allows attenuation in the antenna system.

• Frequency Synthesizer Section (FM)

During FM reception, a combination of synthesizer control IC301 (the frequency dividing ratio is controlled to 1/64 or 1/66 by IC301) allow the slower counter method.

The FM VCO is frequency-divided to a ratio of 1/64 or 1/66 by prescaler IC301.

An output of 4.5 MHz (X101) which becomes a clock pulse for IC301 is divided into 1/180 by the reference frequency divider to produce 25 kHz (all this is processed inside IC301). Since the reception frequency is 87.5 ~ 108.0 MHz and the intermediate frequency (IF) is 10.7 MHz, the oscillator frequency of VCO will be 98.2 ~ 118.7 MHz.

As the overall frequency division ratio is 7856 ~ 9496, the output of the programmable counter inside IC301 will be 25 kHz. This output is compared in phase with a reference frequency of 25 kHz by the phase detector in IC301, and is output to pin 12 of IC301.

The loop filter consisting of Q310 and Q312 converts the signal into a DC voltage signal which in turn controls the tuning circuit in the front end section as a tuning voltage.




Fig. 7




Fig. 8

• Frequency Synthesizer Section (MW)

The MW section employs a direct frequency dividing method. So that the reception frequency is incremented in 9 kHz, the frequency of the phase comparator is 9 kHz. This is produced by dividing 4.5 MHz (the output of X101), a clock frequency of IC301, to 1/500. Since the reception frequency range is 531 ~ 1,602 kHz and the intermediate frequency is selected at 450 kHz, the frequency of the local oscillator (VCO) will be 981 ~ 2,052 kHz.

This output is output from pin 12 of IC5 and enters pin 9 of IC301.

If the frequency dividing ratio of the programmable counter in IC301 is set to 109 ~ 228, the output will be 9 kHz. This frequency is compared in phase with a reference frequency of 9 kHz by the phase comparator and is output from pin 12 of IC301.

The signal is converted into a DC voltage signal by the loop filter consisting of Q310 and Q311, which in turn controls the tuning circuit as a tuning voltage.




Fig. 9

• The Functions of Control IC (PD4041)

PD4041 is a 52-pin flat package C-MOS LSI which controls 10 kHz incremental tuning for FM, 9 kHz incremental tuning for AM. This PLL type frequency synthesizer tuner control IC makes possible 7-segment digital display. Since this IC employs a static method for the display driver, the performance of the receiver is improved.




Fig. 10

• Frequency Synthesizer Section (LW)

The LW section employs a direct frequency dividing method. So that the reception frequency is incremented in 1 kHz, the frequency of the phase comparator is 1 kHz. This is produced by dividing 4.5 MHz (the output of X101), which is a clock frequency of IC301, into 1/4500.

Since the reception frequency range is 155 ~ 281 kHz and the intermediate frequency is selected at 450 kHz, the frequency of the local oscillator (VCO) is 605 ~ 731 kHz. This output is output from pin 12 of IC251 and enters pin 9 of IC301.

If the frequency dividing ratio of the programmable counter in IC301 is set to 605 ~ 731, the output frequency is 1 kHz. This is compared in phase with a reference frequency of 1 kHz by the phase comparator and is output from pin 11 of IC301. The output signal is converted into a DC voltage signal by the loop filter consisting of Q311 and Q312, which in turn controls the tuning circuit as a tuning voltage.




Fig. 11

• Control IC PD4041




Fig. 12


• PIN FUNCTIONS (PD4041)

Pin No.	Pin Name	I/O	Function and Operation
34 } 52 1 } 4	LCD23 } LC5 LCD4 } LCD1	OUT	These are the segment signal output terminals to the LCD panel. Using the matrix of COMON 1 and COMON 2, up to an maximum of 46 dots can be display. The data output format will use PLA for the numerical figures. Symbols and letters data will be directly output from the data memory (RAM).
5 6	COM 2 COM 1	OUT	These are the common signal output terminals to the LCD panel. The three values of GND, 1/2VDD, and VDD (5ms intervals) will be output in 50 Hz cycles. The segment that registers and 1 VDD voltage differential between these terminals and LCD 1-LCD 23, will light up.
7 33	VDD VDD		These are the power supply terminals for the device, supplying a voltage of $5V \pm 10\%$ when the device is operating. The voltage can be lowered to 2.5V when the internal data memory (RAM) is to be maintained (carry out CKSTP command). The device will be recept when a voltage of zero -4.5V is supplied to this terminal, and a program will start from address 0. NOTE: Since pin 7 and pin 33 are connected together inside the device it is sufficient to supply the power voltage to one of these terminals.
8	FM	IN	This accepts the VCO output from 10 ~ 155 MHz (0.5 Vp-p MIN). This is divided down by 1/2 inside the device by using the pulse swallow method. It also features a built-in AC amplifier, and therefore the DC components should be removed from the signal by using a capacitor first before entering the signal into the device.
9	AM	IN	This accepts the VOC output from 0.5 ~ 50 MHz (0.3 Vp-p MIN). This is selected and goes active when the direct dividing method is used. It also features a built-in AC amplifier, and therefore the DC components should be removed from the signal by using a capacitor first before entering the signal into the device.
10	GND		GND Terminal
11 12	EO1 EO2	OUT	This is the charge pump output from the phase detector that forms the PLL. When the divided oscillation frequency is higher than the reference frequency, these terminals will output a high level signal. When the divided oscillation frequency is lower than the reference frequency, these terminals will output a low level signal. Since the same signal will be output from both EO1 and EO2, either terminal can be selected as desired.
13	CE	IN	This is the device select signal input terminal. This terminal should be set to high level when the device is to be operated normally, and set to low level when the device will not be used. However it will not accept an input under 135 μ s.
14	NC		
15 16	XI XO	IN	This the quartz oscillator connection terminal to which is connected a 4.5 MHz quartz oscillator. Adjust the oscillation frequency (4.5 MHz) by monitoring terminal XO.
17	SD	IN	During auto tuning and SDK search, this input terminal detects whether a broadcast station has been received or not. It will stop the tuning when a high level input is received. (Read in SDK STP and AND for SDK search) However, an input must be received within 45ms after the PLL has locked. (Within 75ms for LW reception)
18 19	FM/MW LW	OUT	This is the FM/MW/LW select signal which is output from the device.
20	LOC/DX	OUT	This is the LOC/DX select signal which is output from the device. A high level signal will be output for the LOC mode.
21 } 24	K3 } K0	IN	These are the key return signal input terminals for an external key matrix.
25 } 28 29 30	PB3 } PB0 PC3 PC2	OUT	These are the key return signal source terminals, set to active high. The external diodes can be deleted.
31	SDK	OUT	High level signals from the device are output to this terminal for the SDK mode (Traffic information etc).
32	MUTE	OUT	This muting output terminal, set to active low, eliminates the shock noise when the PLL back is disengaged.

 **PIONEER**

Service Manual

REPAIR & ADJUSTMENTS



The photo shows the model KEH-9300SDK

**ORDER NO.
CRT-387-0**

CASSETTE CAR STEREO WITH FM/MW/LW ELECTRONIC TUNER

KEH-9300SDK WG

KEH-9300 EW

CASSETTE CAR STEREO WITH FM/AM ELECTRONIC TUNER

KEH-9000 ES

- For the circuit and mechanism descriptions, please refer to the service manual (CRT-398).
- 'Dolby' and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.
- Noise Reduction System manufactured under license from Dolby Laboratories Licensing Corporation.

CONTENTS

1. PARTS LIST	1	5. CONNECTION DIAGRAM	
2. DISASSEMBLY	2	(KEH-9300SDK)	16
3. ADJUSTMENT		6. SCHEMATIC CIRCUIT DIAGRAM	
3.1 Dolby NR Level Adjustment	3	(KEH-9300)	20
3.2 Decoder Adjustment	3	7. CONNECTION DIAGRAM	
3.3 FM IF Adjustment	4	(KEH-9300)	24
3.4 FM MPX Adjustment	4	8. SCHEMATIC CIRCUIT DIAGRAM	
3.5 Separation Adjustment	4	(KEH-9000)	28
3.6 FM ARC Adjustment	4	9. CONNECTION DIAGRAM	
3.7 FM Tracking Adjustment	5	(KEH-9000)	32
3.8 AM IF Adjustment	6	10. ELECTRICAL PARTS LIST	36
3.9 AM Tracking Adjustment	7	11. CABINET EXPLODED VIEW	42
4. SCHEMATIC CIRCUIT DIAGRAM		12. TUNER AMP ASSY (1/2) EXPLODED VIEW	45
(KEH-9300SDK)	12	13. TUNER AMP ASSY (2/2) EXPLODED VIEW	47
		14. PACKING METHOD	50

PIONEER ELECTRONIC CORPORATION 4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153, Japan
PIONEER ELECTRONICS (USA) INC. P.O. Box 1760, Long Beach, California 90801 U.S.A.
PIONEER ELECTRONIC (EUROPE) N.V. Keetberglaan 1, 2740 Beveren, Belgium
PIONEER ELECTRONICS AUSTRALIA PTY. LTD. 178-184 Boundary Road, Braeside, Victoria 3195, Australia

EK © DEC. 1983 Printed in Japan

- **Cassette Mechanism Unit**
See the Service Manual CX-146/C (CRT-324) when servicing the cassette mechanism unit.
The differences from the CX-146/C are shown below.

Exploded View (Page 14)

CX-146/C				KEH-9300SDK, 9300, 9000	
Mark	No.	Part No.	Description	Part No.	Description
★ ★	38.	CNL-286	P.C. Board Head	CNP-925	P.C. Board
	41.	CPB-102		CPB-066 or CPB-356	Head

1. PARTS LOCATION

- **KEH-9300SDK**




Fig. 1

- **KEH-9300, 9000**




Fig. 2

2. DISASSEMBLY

• Removing the Case Unit

1. Remove the six screws and then take off the case unit.




Fig. 3

• Removing the Grille Assy

1. Remove the two knobs.
2. Remove the four screws and remove grille assy.




Fig. 4

• Removing the Cassette Mechanism Assy

1. Remove the screw and then take off the SDK Unit.
(Shown in Fig. 4 KEH-9300SDK)
2. Remove the three screws and remove cassette mechanism assy.




Fig. 5

3. ADJUSTMENT

3.1 DOLBY NR LEVEL ADJUSTMENT

• Connection Diagram




Fig. 6

• To Adjust

1. Set the Dolby NR switch to OFF.
2. Playback the Dolby NR level calibration tape CT-150 (400 Hz, 200nwb/m) and adjust VR1 (L ch), VR2 (R ch) so that the mV meter shows $300\text{mV} \pm 1\text{dB}$. ($300\text{mV} = -8.24\text{dBs}$)

3.2 DECODER ADJUSTMENT

• Connection Diagram




Fig. 7

• To Adjust

1. Set the FM SSG as follows:
Carrier: 98 MHz
Modulation (audio): 400 Hz, 60%
Modulation (SK) 57 kHz, 5%
2. Adjust the output of SSG so that the amplitude of indicator of mV meter connected to the terminal No. 4 becomes $2.75\text{mV} \sim 3\text{mV}$.
3. Adjust L401 and L402 so that the amplitude of indicator of mV meter connected to C419 becomes maximum.
4. Adjust VR401 so that SDK lamp lights on.

3.3 FM IF ADJUSTMENT

• Connection Diagram




Fig. 8

• To Adjust

1. Set the Mono switch to MONO.
2. Apply a signal of 98MHz, 400Hz 30% modulation and 60dB (μ V) from the FM SSG and tune 98MHz.
3. Adjust T201 to make the center meter show 0.

3.5 SEPARATION ADJUSTMENT

• Connection Diagram (Show in Fig. 8)

• To Adjust

1. Apply a signal of 98MHz, 1kHz 90% modulation and 19kHz 10% modulation and 60dB (μ V) from the FM SSG. Tune into a frequency of 98MHz.
2. Adjust VR202 to obtain the best separation.
(At this time VR201 is turned in a counterclockwise direction.)

3.4 FM MPX ADJUSTMENT

• Connection Diagram (Show in Fig. 8)

• To Adjust

1. Apply an unmodulated signal of 98MHz and 60dB (μ V) from the the FM SSG. Tune into a frequency of 98MHz.
2. Adjust VR203 to make frequency counter show 19kHz \pm 30Hz.

3.6 FM ARC ADJUSTMENT

• Connection Diagram (Show in Fig. 8)

• To Adjust

1. Set the Mono switch to AUTO.
2. Apply a signal of 98MHz, 1kHz 90% modulation and 19kHz 10% modulation and 35dB (μ V) from the FM SSG. Tune into a frequency of 98MHz.
3. Adjust VR201 to obtain a 5dB separation.

3.7 FM TRACKING ADJUSTMENT

• Connection Diagram




Fig. 9

• To Adjust

Frequency of FM SSG	Displayed Frequency	Adjusting Point	DC V Meter	mV Meter
1.	108 MHz	L3	8.5 ± 0.2 V	
2.	87.5 MHz		2.2 ± 0.6 V check	
3. 90 MHz (400 Hz, 100% modulation) output level 5 ~ 10 dB (μ V)	90 MHz	L1, L2		Maximum output
4. 106 MHz (400 Hz, 100% modulation) output level 5 ~ 10 dB (μ V)	106 MHz	TC1, TC2		Maximum output
5. Repeat steps (3) and (4) alternately so that the mV meter indicates maximum output.				
6. 98 MHz (400 Hz, 100% modulation) output level 5 ~ 10 dB (μ V)	98 MHz	T2		Maximum output



3.8 AM IF ADJUSTMENT

- **Connection Diagram**

IF Generator Scope

Sweep center frequency 450 kHz
Input gain. 0.3 Vp-p/cm




Fig. 10

- **To Adjust**

1. Apply minimum output signal required to check generator scope U curve and adjust T259 and T260 so that curve amplitude is at maximum point and there is optimum symmetry.

3.9 AM TRACKING ADJUSTMENT

• Connection Diagram




Fig. 11

NOTICE:

Select C1 so that total capacity of 80pF is attained from the direction of the receiver jack.

Z: Output impedance of the SSG.

• To Adjust (In case of MW)


Frequency of AM SSG	Displayed Frequency	Adjusting Point	DC V Meter	mV Meter
1.	531 kHz	For Confirmation Only	More than 0.8V	
2. 603 kHz (400 Hz, 30% modulation) output level 25 dB (μ V)	603 kHz	T253, T255		Maximum output
3.	1,602 kHz	For Confirmation Only	More than 8.5V	

• To Adjust (In case of LW.....KEH-9300SDK, 9300)


Frequency of AM SSG	Displayed Frequency	Adjusting Point	DC V Meter	mV Meter
1.	153 kHz	For Confirmation Only	More than 2.5V	
2. 218 kHz (400 Hz, 30% modulation) output level 25 dB (μ V)	218 kHz	T254, T256		Maximum output
3.	281 kHz	For Confirmation Only	More than 8.5V	

• IC's and Transistors


2SD1012




2SA937F
2SB822F
2SC2021F
2SD1055F




2SC2634NL




2SA1048
2SC2458




2SK241




2SD1276




2SC2570




2SK330




2SK163




P003




2SB709
2SC2712
2SD601



2SD655
2SD667




2SK30A




Part No.	Indication (Type No., hFE)
2SB709-AQ	AQ
2SB709-AR	AR
2SB709-AS	AS
2SC2712-LG	LG
2SC2712-LL	LL
2SC2712-LY	LY
2SD601-YQ	YQ
2SD601-YR	YR
2SD601-YS	YS


PA0014




PA0013




NR9200




PA0015




CWW-173




PA4009




TA7270P




TA7271P




PA4009




TA75558P



MB3106MF




AN6540




IC's marked by * are MOS type.
Be careful in handling them because they are very
liable to be damaged by electrostatic induction.


TA7270P




S0280




S551




TA7271P



HA12434



* PD4041



4. SCHEMATIC CIRCUIT DIAGRAM (KEH-9300SDK)







Fig. 12

5. CONNECTION DIAGRAM (KEH-9300SDK)


FM FRONT END (CWB-151)




FM FRONT END (CWB-151)

	1	2	3	4	5	6	7	8	9	10
IC 2	0	0	0	0	0	3.3	3.3	3.3	0	0
IC 2	5.7	8.5	8.2	3.2	0	2.5	2.7	0	0	0


(V)



HEAD UNIT



KEY BOARD UNIT (CWS-192)




TUNER UNIT

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
IC201	2.2	2.2	0	2.2	5.0	5.0	5.0	4.7	4.7	4.7	0	1.1	8.3	1.7	0	0.3	0.4	0.4	0	0
IC202	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	3.4	1.4	1.3	0	0	0	0.4	0	0	0
IC203	0.4	4.3	2.3	2.3	0	2.3	2.3	1.7	2.3	3.5	3.5	8.5	0.5	2.3	2.9	0	0	0	0	2.3
IC251	0	0.3	8.3	2.3	1.3	1.6	3.7	3.7	8.3	6.5	2.3	8.0	2.7	1.5	0	0	0	0	0	0
IC 2	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0	2.6	4.0


(V)

TUNER UNIT

IC, Q	IC201	IC1	Q301	Q302	Q304	Q204	Q203	Q252	Q256	Q254	Q255	Q257	Q317	Q251	Q314	Q311	Q313	IC251	Q312	Q8	Q7	Q6	Q260	Q5	IC2
ADJ	VR201	VR203	T201	VR202	T254	T254	T253	T255	VR2	T260	VR1														



IC1: MB3106M	IC2: NR9200	IC3: AN6540	IC201: PA0013	IC202: PA0014	IC203: PA0015	IC251: HA1243	IC301: PD4041
Q1~4, 7, 8, 11: 2SC2458	Q5: 2SD667	Q6: 2SA1048	Q9: 2SC2712-LG or 2SD601-YQ	Q10: 2SB709-AQ	Q12: 2SD1276	Q201~204: 2SC2458	Q205: 2SC2712-LG or 2SD601-YQ
Q251: 2SK163	Q252~260: 2SC2458	Q301~304, 313: 2SA1048	Q305~307, 312, 315, 316: 2SC2458	Q308, 309: 2SC2712-LG or 2SD601-YQ	Q310: 2SK330-Y	Q311: 2SK330-Y	Q312: 2SK330-Y
D1: RD4RIE82	D2: IS1555	D3: RD4RIE82	D4: US1040, IS1555 or DS442	D5: SM-1A-02	D202~205: US1040, IS1555 or DS442	D301: 304, 311: MA151WA	D302, 303, 306, 312: US1040, IS1555 or DS442
D251~254: IS1555	D255: KVI23525	D301: 304, 311: MA151WA	D302, 303, 306, 312: US1040, IS1555 or DS442	D303: RD3RBE2	D307: RD5RBE2	D308: MA151WA	D309: RD6R2E2
D310: RD4R7E1	D313: US1040, IS1555 or DS442						



A

B

C

D

Fig. 13

20







Fig. 14

7. CONNECTION DIAGRAM(KEH-9300)

FM FRONT END(CWB-151)

IC, Q IC1 Q1 Q2 IC2 Q3
 ADJ L1 TC1 L2 TC2 T2 L3



IC1: CWW-173 IC2: PA400Q-A Q1: P003 Q2: 2SC2570
 Q3: 2SK241-GR D1: 3KV1310-6

FM FRONT END (CWB-151)

	1	2	3	4	5	6	7	8	9	10
IC2	0	0	0	0	0	3.3	3.3	3.3	0	0
IC2	5.7	8.5	8.2	8.2	0	2.5	2.7	0	0	0

(V)

TUNER UNIT


	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
IC201	2.2	2.2	0	2.2	5.0	5.0	5.0	4.7	4.7	4.7	0	1.1	8.3	1.7	0	0.3	0.4	0.4	0	0
IC202	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	3.4	1.4	1.3	0	0	0	0	0.4	0	0
IC203	0.4	4.3	2.3	2.3	0	2.3	2.3	1.7	2.3	3.5	3.5	8.5	0.5	2.3	2.9	0	0	0	2.3	0
IC251	0	0.3	8.3	2.3	1.3	1.6	3.7	3.7	8.3	6.5	2.3	8.0	4.2	2.7	1.5	0	0	0	0	4.2
IC2						2.6	4.0													

(V)


TUNER UNIT

IC, Q IC201 IC1 Q301 Q302 Q202 Q201 Q205 Q256 Q254 Q255 Q257 Q317 Q251 Q11 Q310 Q253 Q307 Q314 Q311 Q313 IC251 Q312 Q8 Q7 Q6 Q260 Q5 IC2


ADJ VR201 VR203 T201 VR202 T254 T254 T253 T255 VR2 T260 VR




HEAD UNIT



REMOTE SWITCH ASSY




KEY BOARD UNIT (CWS-197)



D1, 2: IS1555 or IS2076 D3, 5, 6: BG3422K D4: AA3422K D7: 14: BG5724K

IC1: MB3106M IC2: NR4200 IC3: AN6540 IC201: PA0013 IC202: PA0014 IC203: PA0015 IC251: HA12434 IC301: PD4041
 Q1-4, 7, 8, 11: 2SC2458 Q5: 2SD667 Q6: 2SA1048 Q4: 2SC2712-LG or 2SD601-Y Q10: 2SB709-AQ Q12: 2SD1276 Q201-204: 2SC2458
 Q205: 2SC2712-LG or 2SD601-Y Q251: 2SK163 Q252-260: 2SC2458 Q301, 302, 304, 313: 2SA1048 Q306, 307, 312, 316: 2SC2458
 Q308, 309: 2SC2712-LG or 2SD601-Y Q310: 311: 2SK330-Y Q314: 2SD1055F Q317, 318: 2SB822F
 D1: RD4RIE2 D2: IS1555 D3: RD4RIE2 D4: US1040, IS1555 or DS442 D5: SM-1A-D2 D202-205: US1040, IS1555 or DS442
 D251-254: IS1555 D255: KVI235Z5 D301, 304: MA151WA D302, 306, 312: US1040, IS1555 or DS442 D305: RD3R3EB2
 D307: RD5R6EB2 D308: MA151WK D309: RD6R2EB2 D310: RD4R7EB1 D313: US1040, IS1555 or DS442



A


B


C

D

Fig. 15

8. SCHEMATIC CIRCUIT DIAGRAM (KEH-9000)





- SWITCHES**
- **SWITCH UNIT**
S101: 2SP/4SP SELECTOR SWITCH.....2SP-4SP
 - **SWITCH P.C. BOARD**
S1: TAPE/TUNER SWITCH.....TAPE-TUNER
S2: KEY OFF SWITCH.....ON-OFF
 - **VOLUME UNIT**
S1: RADIO SWITCH.....ON-OFF
 - **HEAD UNIT**
S1: FWD/REV SWITCH.....FWD-REV
 - **TUNER UNIT**
S1: MONO SWITCH.....MONO-AUTO
S2: METAL SWITCH.....ON-OFF
S3: DOLBY NR SWITCH.....ON-OFF
 - **MISCELLANEOUS**
S1: FF/REW SWITCH.....ON-OFF
- The underlined indicates the switch position.

NOTE :


- Indicate a chip transistor
- Indicate a chip diode
- Indicate a chip resistor
- Indicate a chip capacitor

Fig 16

9. CONNECTION DIAGRAM (KEH-9000)

FM FRONT END (CWB-151)

IC,Q IC1 Q1 Q2 IC2 Q3
ADJ L1 TC1 L2 TC2 T2 L3




IC1: CWW-173 IC2: PA4004-A Q1: P003 Q2: 2SC2570
Q3: 2SK241-GR DI: 3: KV1310-6

FM FRONT END (CWB-151)


	1	2	3	4	5	6	7	8	9	10
IC2		0	8.3			0	3.3	3.3	3.3	0
IC2	5.7	8.5	8.2	3.2	0	2.5	2.7		0	

(V)


REMOTE SWITCH ASSY



HEAD UNIT



KEY BOARD UNIT (CWS-194)



D1, 2: IS1555 or IS2076 D3, 5, 6: BG3422K D4: AA3422K D7 ~ 14: BG5724K


TUNER UNIT

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
IC201	2.2	2.2	2.2	0		2.2	5.0	5.0	5.0	4.7	4.7	4.7	0	1.1	8.3	1.7	0	0.3	0.4	0.4
IC202	4.0	4.0	4.0	4.0	4.0	4.0	4.0		4.0	4.0		3.3	3.4	1.4	1.3	3.3	3.7	0	0.4	0
IC203		0.4	4.3	2.3	2.3	0	2.3	2.3	1.7	2.3	3.5	3.5	8.5	0.5	2.3	2.9		0	0	2.3
IC251	2.3	0	0.3	8.3	2.3	1.3	1.5	3.7	3.7	0	8.3		2.3	8.0	8.0	2.7	1.5	0		
IC 2									4.0						4.2	4.2		7.8		4.2

(V)


TUNER UNIT

IC,Q IC201 IC1 Q301 Q302 Q204 Q252 Q205 Q317 Q251 Q11 Q253 IC3 Q312 Q8 Q7 Q6 Q260 Q5 IC2
ADJ VR201 VR203 T201 VR202 T254 T253 T255 VR2 T260 VR1




IC1: MB3106M IC2: NR4200 IC3: AN6540 IC201: PA0013 IC202: PA0014 IC203: PA0015 IC251: HA12434 IC301: PD4041
Q1~4: 7, 8, 11: 2SC2458 Q5: 2SD667 Q6: 2SA1048 Q7: 2SC2712-LG or 2SD601-YQ Q8: 2SD709-AQ Q9: 2SD1276 Q10: 2SD2458
Q205: 2SC2712-LG or 2SD601-YQ Q251: 2SK163 Q252: 253, 254, 255, 256: 2SC2458 Q301, 302, 304, 318: 2SA1048 Q312, 316: 2SC2458
Q317, 318: 2SB822F Q319, 318: 2SD1055F Q314: 2SD1055F Q315: 2SD1055F Q316: 2SD1055F Q317: 2SD1055F Q318: 2SD1055F
D1: RD4R1EB2 D2: RD4R1EB2 D3: RD4R1EB2 D4: RD4R1EB2 D5: RD4R1EB2 D6: RD4R1EB2 D7: RD4R1EB2 D8: RD4R1EB2 D9: RD4R1EB2 D10: RD4R1EB2
D11: RD4R1EB2 D12: RD4R1EB2 D13: RD4R1EB2 D14: RD4R1EB2 D15: RD4R1EB2 D16: RD4R1EB2 D17: RD4R1EB2 D18: RD4R1EB2 D19: RD4R1EB2 D20: RD4R1EB2
D21: RD4R1EB2 D22: RD4R1EB2 D23: RD4R1EB2 D24: RD4R1EB2 D25: RD4R1EB2 D26: RD4R1EB2 D27: RD4R1EB2 D28: RD4R1EB2 D29: RD4R1EB2 D30: RD4R1EB2
D31: RD4R1EB2 D32: RD4R1EB2 D33: RD4R1EB2 D34: RD4R1EB2 D35: RD4R1EB2 D36: RD4R1EB2 D37: RD4R1EB2 D38: RD4R1EB2 D39: RD4R1EB2 D40: RD4R1EB2
D41: RD4R1EB2 D42: RD4R1EB2 D43: RD4R1EB2 D44: RD4R1EB2 D45: RD4R1EB2 D46: RD4R1EB2 D47: RD4R1EB2 D48: RD4R1EB2 D49: RD4R1EB2 D50: RD4R1EB2
D51: RD4R1EB2 D52: RD4R1EB2 D53: RD4R1EB2 D54: RD4R1EB2 D55: RD4R1EB2 D56: RD4R1EB2 D57: RD4R1EB2 D58: RD4R1EB2 D59: RD4R1EB2 D60: RD4R1EB2
D61: RD4R1EB2 D62: RD4R1EB2 D63: RD4R1EB2 D64: RD4R1EB2 D65: RD4R1EB2 D66: RD4R1EB2 D67: RD4R1EB2 D68: RD4R1EB2 D69: RD4R1EB2 D70: RD4R1EB2
D71: RD4R1EB2 D72: RD4R1EB2 D73: RD4R1EB2 D74: RD4R1EB2 D75: RD4R1EB2 D76: RD4R1EB2 D77: RD4R1EB2 D78: RD4R1EB2 D79: RD4R1EB2 D80: RD4R1EB2
D81: RD4R1EB2 D82: RD4R1EB2 D83: RD4R1EB2 D84: RD4R1EB2 D85: RD4R1EB2 D86: RD4R1EB2 D87: RD4R1EB2 D88: RD4R1EB2 D89: RD4R1EB2 D90: RD4R1EB2
D91: RD4R1EB2 D92: RD4R1EB2 D93: RD4R1EB2 D94: RD4R1EB2 D95: RD4R1EB2 D96: RD4R1EB2 D97: RD4R1EB2 D98: RD4R1EB2 D99: RD4R1EB2 D100: RD4R1EB2


SWITCH P.C.BOARD



SWITCH UNIT



AMP UNIT




AMP UNIT

IC101	1	2	3	4	5	6
	1.5	1.5	3.6	0	1.4	1.4
IC101	7	8	9	10	11	12
	0	7.3	13.6	14.3	13.6	7.3


(V)

TWO SPEAKER SYSTEM


FOUR SPEAKER SYSTEM



VOLUME UNIT



GRAPHIC EQ. UNIT (CWG-127)



- NOTE:
- Indicate a chip transistor
 - Indicate a chip diode
 - Indicate a chip resistor
 - Indicate a chip capacitor

Fig. 17

A

B

C

D

10. ELECTRICAL PARTS LIST

NOTE:

When ordering resistors, first convert resistance values into code form as shown in the following examples.

Ex. 1 When there are 2 effective digits (any digit apart from 0), such as 560 ohm and 47k ohm (tolerance is shown by J = 5%, and K = 10%).

560Ω 56 × 10¹ 561 RD1/4PS 5 6 1 J

47kΩ 47 × 10³ 473 RD1/4PS 4 7 3 J

0.5Ω 0R5 RN2H 0 R 5 K

1Ω 010 RS1P 0 1 0 K

Ex. 2 When there are 3 effective digits (such as in high precision metal film resistors).

5.62kΩ 562 × 10¹ RN1/4SR 5 6 2 1 F

- For your Parts Stock Control, the fast moving items are indicated with the marks ★ ★ and ★.
- ★ ★: GENERALLY MOVES FASTER THAN ★.
- This classification shall be adjusted by each distributor because it depends on model number, temperature, humidity, etc.
- Parts whose parts numbers are omitted are subject to being not supplied.

FM Front End (CWB-151)

MISCELLANEOUS

Mark	Symbol & Description	Part No.
★ ★	IC1	CWW-173
★ ★	IC2	PA4009
★ ★	*Q1	P003
★ ★	Q2	2SC2570
★ ★	Q3	2SK241-GR
★	D1 — D3	KV1310-6
	L1 Coil	CTC-189
	L2 Coil	CTC-190
	L3 Coil	CTC-191
	L4 Chip Inductor	CTF-185
	L5 Chip Inductor	CTF-186
	T1 Transformer	CTC-186
	T2 IF Transformer	CTC-187
	TC1, TC2 Trimmer	CCG-098
	CF1, CF2 Ceramic Filter	CTF-182

RESISTORS

Mark	Symbol & Description	Part No.
	R1, R2, R4 — R11, R14 Chip Resistor	RS1/8S□□□J
	*R3, R12, R13	RD1/6PS□□□J

Caution:

Transistor *Q1 and resistor * R3 used mutually in the following assembly.

Q1	R3
P003-A	RD1/6PS473J
P003-B	RD1/6PS393J

CAPACITORS

Mark	Symbol & Description	Part No.
	C1, C2 Chip Capacitor	CCSSH220J50
	C3, C8 Chip Capacitor	CCSCH050C50
	C4, C5, C11, C15, C20	CKSYB222K50
	C6 Chip Capacitor	CCSCH040C50
	C7, C10 Chip Capacitor	CKSYB103K50
	C9 Chip Capacitor	CCSSH560J50
	C12, C18 Chip Capacitor	CCSTH150J50
	C13 Chip Capacitor	CCSTH330J50
	C14 Chip Capacitor	CCSTH120J50
	C16, C19, C21 Chip Capacitor	CKSYF223Z50
	C17 Chip Capacitor	CCSUJ080D50
	C22	CEA2R2M35LS
	C23	CEA3R3M25LS

Volume Unit

MISCELLANEOUS

Mark	Symbol & Description	Part No.
★ ★	Q101, Q102	2SC2458
★ ★	Q103, Q104	2SD655
★ ★	Q113	2SC2634NC
★	D101	RD9R1EB2
★ ★	VR 101/S1 Volume/Switch Volume, 50 kΩ(W) × 2, 20 kΩ(B) (Fader, Balance, Volume/Radio Switch)	CCS-362

RESISTORS (KEH-9300SDK)

Mark	Symbol & Description	Part No.
	R101 — R114, R149, R150 Chip Resistor	RS1/8S□□□J
	R501 — R505 Chip Resistor 0Ω	RS1/8S0R0J

RESISTORS (KEH-9300, 9000)

Mark	Symbol & Description	Part No.
	R101 — R122, R149, R150 Chip Resistor	RS1/8S□□□J
	R501, R503 — R504 Chip Resistor 0Ω	RS1/8S0R0J

CAPACITORS

Mark	Symbol & Description	Part No.
	C101, C102, C105, C106	CEA010M50LS
	C103, C104	CEA3R3M50LS
	C142	CEA470M16LS
	C143	CEA101M10L2

Switch Unit

MISCELLANEOUS

Mark	Symbol & Description	Part No.
★ ★	Q105, Q106	2SA937F
★ ★	Q107, Q108	2SC2021F
★ ★	S101 Switch (2SP/4SP Selector)	CSH-070

RESISTORS (KEH-9300SDK)

Mark	Symbol & Description	Part No.
	R115 — R132 Chip Resistor	RS1/8S□□□J
	R506 — R509 Chip Resistor 0Ω	RS1/8S0R0J

RESISTORS (KEH-9300, 9000)

Mark	Symbol & Description	Part No.
	R115 — R124, R127 — R132 Chip Resistor	RS1/8S□□□J
	R506 — R509 Chip Resistor 0Ω	RS1/8S0R0J

CAPACITORS

Mark	Symbol & Description	Part No.
	C107, C108	CEA100M25LS

Amp Unit

MISCELLANEOUS

Mark	Symbol & Description	Part No.
★ ★	IC101	TA7270P
★ ★	IC102	TA7271P
★ ★	Q109, Q110	2SD1012
★ ★	Q111, Q112	2SC2458
★	D102	RD6R8EB2

RESISTORS

Mark	Symbol & Description	Part No.
	R133 — R143, R145 — R148 Chip Resistor	RS1/8S□□□J
	R144	RD1/4PM□□□J
	R510, R571 Chip Resistor 0Ω	RS1/8S0R0J

CAPACITORS

Mark	Symbol & Description	Part No.
	C109 — C112 Chip Capacitor	CKSYB681K50
	C113 — C116	CEAR47M50LS2
	C117, C118	COMA473J50L
	C119 — C122, C125 — C128	CEA101M10L2
	C123, C124	CEA470M16L2
	C129 — C132	COMA224K50L
	C133 Feed through Capacitor	CCL-123
	C138	CEA222M16L2
	C139, C140	COMA104K50L
	C141	CEA100M16L2
	C144 Chip Capacitor	CKSYB223K25

Door Unit (CXD-120)

Mark	Symbol & Description	Part No.
★	D1, D2 LED	BG1524K

Remote Switch Assy

Mark	Symbol & Description	Part No.
★ ★	S1, S2 Switch	CS3-176

Key Board Unit (CWS-192) (KEH-9300SDK)

Key Board Unit (CWS-197) (KEH-9300)

Key Board Unit (CWS-194) (KEH-9000)

Mark	Symbol & Description	Part No.
★	LCD (KEH-9300SDK, 9300)	FTI-6082H
★	LCD (KEH-9000)	FTI-6081H
★	D1, D2	1S555 or 1SD76
★	D3, D5, D6 LED	BG422K
★	D4 LED	AA422K
★	D7 — D14 LED	BG724K
★ ★	IL1 — IL5 Lamp 14V 40mA	CE-147
	R1 — R3	RD/4PM□□□J

Head Unit

Mark	Symbol & Description	Part No.
★ ★	HD1 Head	CP-066
★ ★	S1 Switch (FWD/REV)	CS-070

Switch P.C. Board

Mark	Symbol & Description	Part No.
★ ★	S1 Switch (Tape/Tuner)	CSF-014
★ ★	S2 Switch (Key Off)	CSN-071

SDK Unit (KEH-9300SDK)

Mark	Symbol & Description	Part No.
★ ★	IC401	S0280
★ ★	IC402	TA75558P
★ ★	IC403	S551
★ ★	Q401 — Q404, Q408 — Q410	2SC2458
★ ★	Q405	2SK30A-O
★ ★	Q406	2SA1048-GR
★ ★	Q407	2SA1048
★ ★	Q411 — Q413 Chip Transistor	2SC2712-LG or 2SC2712-LL or 2SC2712-LY or
★	D401 — D405, D410	2SD601-YQ or 2SD601-YR or 2SD601-YS 1S1555 or US2076 or
★	D406 — D408	1S2473 US1040 or 1S1555 or DS442
★	D409 Chip Diode	MA151WA
★ ★	L401, L402 Coil CF401 Ceramic Resonator VR401 Semi-fixed, 4.7kΩ (B)	CTF-125 CTF-109 CCP-243

RESISTORS

Mark	Symbol & Description	Part No.
	R401 — R437, R439 — R444 Chip Resistor	RS1/8S□□□J
	R551 — R563, R570, R572 Chip Resistor 0Ω	RS1/8S0R0J

CAPACITORS

Mark	Symbol & Description	Part No.
	C401, C415, C425 Chip Capacitor	CKSYB223K25
	C402, C403, C406 Chip Capacitor	CCSSL391J50
	C404 Chip Capacitor	CKSYB681K50
	C405, C417	CEA220M16LS
	C407	CEA101M16L2
	C408, C414 Chip Capacitor	CKSYB103K50
	C409, C412	CQSA102J50
	C410, C413	CCDLH680J50L
	C411	CCDLH120J50L
	C416	CQSA151J50

Mark	Symbol & Description	Part No.
	C418	CEAR33M50LS2
	C419	CEA0R1M50LS2
	C420 Chip Capacitor	CKSYF104Z25
	C421	CQMA103J50L
	C422	CQMA333J50L
	C423	CEA100M25LS
	C424, C427	CEA010M59LS2
	C426	CEA100M16L2

Tuner Unit (KEH-9300SDK, 9300)

MISCELLANEOUS

Mark	Symbol & Description	Part No.
★ ★	IC1	MB3106M
★ ★	IC2	NR9200
★ ★	IC3	AN6540
★ ★	IC201	PA0013
★ ★	IC202	PA0014
★ ★	IC203	PA0015
★ ★	IC251	HA12434-A or HA12434-B PD4041
★ ★	IC301	2SC2458
★ ★	Q1 — Q4, Q7, Q8, Q11	
★ ★	Q5	2SD667
★ ★	Q6, Q301, Q302, Q304, Q313	2SA1048
★ ★	Q9, Q205, Q308, Q309 Chip Transistor	2SC2712-LG or 2SC2712-LL or 2SC2712-LY or
★ ★	Q10 Chip Transistor	2SD601-YQ or 2SD601-YR or 2SD601-YS 2SB709-AQ or 2SB709-AR or
★ ★	Q12	2SB709-AS
★ ★	Q201 — Q204, Q252 — Q260, Q306, Q307, Q312, Q316	2SD1276 2SC2458
★ ★	Q251	2SK163
★ ★	Q303 (KEH-9300SDK)	2SA1048
★ ★	Q305 (KEH-9300SDK), Q315 (KEH-9300SDK)	2SC2458
★ ★	Q310, Q311	2SK330-Y
★ ★	Q314	2SD1055F
★ ★	Q317, Q318	2SB822F
★	D1	RD9R1EB2
★	D2, D4, D202 — D205	1S1555 or US1040 or DS442
★	D3	RD9R1EB3
★	D5	SM-1A-02

Mark	Symbol & Description	Part No.
★	D251 — D254	1S1555
★	D255	KV1235Z5-A or KV1235Z5-B or KV1235Z5-C or KV1235Z5-D or KV1235Z5-E or KV1235Z5-F
★	D301, D304, D311 (KEH-9300 SDK) Chip Diode	MA151WA
★	D302 (KEH-9300SDK), D303, D306, D312, D313	US1040 or 1S1555 or DS442
★	D305	RD3R3EB2
★	D307	RD5R6EB2
★	D308 Chip Diode	MA151WK
★	D309	RD6R2EB2
★	D310	RD4R7EB1
	L201 Ferri-Inductor, 15μH	CTF-156
	L202 Ferri-Inductor, 2.7μH	CTF-155
	L251 Ferri-Inductor, 100μH	CTF-157
	T201 Coil	CTC-177
	T251 Coil	CTB-149
	T252 Coil	CTB-161
	T253, 255 Coil	CTB-150
	T254, 256 Coil	CTB-151
	T257 Coil	CTB-164
	T258 Coil	CTB-165
	T259 AM Coil	CTE-139
	T260 AM Coil	CTE-140
	IB1	CWW-206
	RL1 Relay	CSR-020
	CR201	CWW-183
	CR202	CWW-182
	CF201 Ceramic Filter	CTF-182
	CF251 Filter	CTF-100
	CF252 Filter	CTF-165
★ ★	S1 — S3 Switch	CSG-207
★ ★	VR1, VR2 Semi-fixed, 33kΩ(B)	CCP-248
★ ★	VR201 Semi-fixed, 22kΩ(B)	CCP-247
★ ★	VR202 Semi-fixed, 1.5kΩ(B)	CCP-240
★ ★	VR203 Semi-fixed, 6.8kΩ(B)	CCP-244
	X301 Crystal Resonator	CSS-022

RESISTORS (KEH-9300SDK)

Mark	Symbol & Description	Part No.
	R1 — R14, R16 — R23, R25 — R35, R38 — R43, R46 — R65, R67, R68, R201 — R206, R208 — R210, R212, R214 — R225, R251 — R284, R288, R301 — R323, R325 — R336, R338 — R341 Chip Resistor	RS1/8S□□□J
	R44, R66, R207, R211, R324 R285 — R287 R511 — R545, R547 — R549, R564 — R566 Chip Resistor 0Ω	RD1/4PM□□□J RD1/6VS□□□J RS1/8S0R0J

RESISTORS (KEH-9300)

Mark	Symbol & Description	Part No.
	R1 — R14, R16 — R23, R25 — R35, R38 — R43, R46 — R65, R67, R68, R201 — R206, R208 — R210, R212, R214 — R225, R251 — R284, R288, R301 — R304, R306 — R312, R314 — R323 R325 — R333, R336 — R340 Chip Resistor	RS1/8S□□□J
	R44, R66, R207, R211, R324 R285 — R287 R511 — R549, R564, R565 Chip Resistor	RD1/4PM□□□J RD1/6VS□□□J RS1/8S0R0J

CAPACITORS

Mark	Symbol & Description	Part No.
	C1, C2 Chip Capacitor	CKSYB681K50
	C3, C4, C11, C13 — C15, C19, C20	CEA470M16LS
	C5, C6	CEANL4R7M50LL
	C7, C8, C30 Chip Capacitor	CKSYB103K50
	C9, C10, C31 Chip Capacitor	CKSYB223K25
	C12	CEA221M10L2
	C16, C17, C25	CEA100M25LS
	C18	CEA4R7M35LS
	C21	CEA010M50LS2
	C22	CEA221M16L2
	C23, C24 Chip Capacitor	CKSYF104Z25
	C26 Feed through Capacitor	CCL-124
	C29	CEA220M16LS
	C201 Chip Capacitor	CKSYF104Z25
	C202, C204, C211	CEA010M50LS2
	C203, C213 Chip Capacitor	CCSSL101K50
	C205, C217	CEA100M25LS
	C206 — C210 Chip Capacitor	CKSYB223K25
	C212, C221 Chip Capacitor	CKSYB103K50
	C214	CEA2R2M50LS2
	C215, C230	CEA220M16LS
	C216 Chip Capacitor	CKSYB681K50
	C218	CEA4R7M35NPLL
	C219, C220	CEA470M16LS
	C222 — C224 Chip Capacitor	CKSYB822K50
	C225	CQMA183J50L
	C226	CSZA010M25
	C227	CSZA1R5M25
	C228	CSZA2R2M25
	C229	CQSA102J50
	C231, C232	CEA3R3M50LS
	C251, C254, C257, C274, C277, C286 Chip Capacitor	CKSYB223K25
	C252, C288 Chip Capacitor	CKSYB103K50
	C253 Chip Capacitor	CKSYB332K50
	C255, C256, C260 — C264, C275, C276 Chip Capacitor	CKSYF473Z50
	C258, C273, C289 Chip Capacitor	CKSYF104Z25
	C259	CEA221M10L2
	C265, C282	CEA470M16LS

Mark	Symbol & Description	Part No.
	C266 Chip Capacitor	CCSCH680J50
	C267	CCDRH510J50L
	C268 Chip Capacitor	CCSPH270J50
	C269	CQPA331G100
	C270	CCDCH070D50L
	C272	CCDSH430J50L
	C278, C280, C287, C293 Chip Capacitor	CKSYF473Z50
	C279	CEA010M50LS2
	C281	CEAR47M50LS2
	C283	CEA220M16LS
	C284	CEA3R3M50LS
	C285	CEAR33M50LS2
	C290	CEA101M10L2
	C291, C292 Chip Capacitor	CCSSH090D50
	C302, C317, C318 Chip Capacitor	CKSYF473Z50
	C303 Chip Capacitor	CCSCH270J50
	C304 Chip Capacitor	CCSCH220J50
	C305	CEAR15M50LS2
	C306	CSZA010M25
	C307, C308	CSZA100M25
	C309, C314, C315 Chip Capacitor	CKSYB103K50
	C310, C311	CEA220M16LS
	C312	CEA4R7M35LS
	C313	CEA221M16L2
	C316	CEA221M6R3L2

Tuner Unit (KEH-9000)

MISCELLANEOUS

Mark	Symbol & Description	Part No.
★ ★	IC1	MB3106M
★ ★	IC2	NR9200
★ ★	IC3	AN6540
★ ★	IC201	PA0013
★ ★	IC202	PA0014
★ ★	IC203	PA0015
★ ★	IC251	HA12434-A or HA12434-B
★ ★	IC301	PD4041
★ ★	Q1 — Q4, Q7, Q8, Q11	2SC2458
★ ★	Q5	2SD667
★ ★	Q6	2SA1048
★ ★	Q9, Q205 Chip Transistor	2SC2712-LG or 2SC2712-LL or 2SC2712-LY or 2SD601-YQ or 2SD601-YR or 2SD601-YS
★ ★	Q10 Chip Transistor	2SB709-AQ or 2SB709-AR or 2SB709-AS
★ ★	Q12	2SD1276
★ ★	Q201 — Q204, Q252, Q253, Q259, Q260	2SC2458
★ ★	Q251	2SK163

Mark	Symbol & Description	Part No.
★ ★	Q301, Q302, Q304, Q313	2SA1048
★ ★	Q311	2SK330-Y
★ ★	Q312, Q316	2SC2458
★ ★	Q314	2SD1055F
★ ★	Q317, Q318	2SB822F
★	D1	RD9R1EB2
★	D2, D4, D202 — D205, D306, D312, D313	1S1555 or DS442 or US1040
★	D3	RD9R1EB3
★	D5	SM-1A-Q2
★	D251 — D254	1S1555
★	D255	KV1235Z-A or KV1235Z-B or KV1235Z-C or KV1235Z-D or KV1235Z-E or KV1235Z-F
★	D301, D304 Chip Diode	MA151VA
★	D305	RD3R3EB2
★	D307	RD5R6EB2
★	D308 Chip Diode	MA151VK
★	D309	RD6R2EB2
★	D310	RD4R7EB1
	L201 Ferri-Inductor, 15 μ H	CTF-156
	L201 Ferri-Inductor, 2.7 μ H	CTF-155
	L202 Ferri-Inductor, 100 μ H	CTF-157
	T201 Coil	CTC-171
	T251 Coil	CTB-143
	T252 Coil	CTB-161
	T253, T255 Coil	CTB-151
	T257 Coil	CTB-163
	T259 AM Coil	CTE-133
	T260 AM Coil	CTE-143
	IB1	CWW-26
	RL1 Relay	CSR-02
	CR201	CWW-83
	CR202	CWW-82
	CF201 Ceramic Filter	CTF-18
	CF251 Filter	CTF-10
	CF252 Filter	CTF-16
	S1 — S3 Switch	CSG-27
★ ★	VR1, VR2 Semi-fixed, 33k Ω (B)	CCP-24
★ ★	VR201 Semi-fixed, 22k Ω (B)	CCP-27
★ ★	VR202 Semi-fixed, 1.5k Ω (B)	CCP-24
★ ★	VR203 Semi-fixed, 6.8k Ω (B)	CCP-24
	X301 Crystal Resonator	CSS-02

RESISTORS

Mark	Symbol & Description	Part No.
	R1 — R14, R16 — R23, R25 — R35, R38 — R43, R46 — R65, R68, R69, R201 — R206, R208 — R210, R212, R214 — R225, R251 — R256, R261 — R274, R282 — R284, R288, R301 — R304,	RS1/8S□□□J
	R306 — R308, R314 — R318, R323, R325, R326 — R333, R336, R338 — R340 Chip Resistor R44, R66, R207, R211 R285 — R287	RD1/4PM□□□J RD1/6VS□□□J
	R511 — R526, R528, R531 — R549, R564, R565 Chip Resistor 0Ω	RS1/8S0R0J

CAPACITORS


Mark	Symbol & Description	Part No.
	C1, C2 Chip Capacitor C3, C4, C11, C13 — C15, C19, C20 C5, C6 C7, C8, C30 Chip Capacitor	CKSYB681K50 CEA470M16LS CEANL4R7M50LL CKSYB103K50
	C9, C10, C31 Chip Capacitor C12 C16, C17, C25 C18 C21	CKSYB223K25 CEA221M10L2 CEA100M25LS CEA4R7M35LS CEA010M50LS2
	C22 C23, C24 Chip Capacitor C26 Feed through Capacitor C29 C201 Chip Capacitor	CEA221M16LS CKSYF104Z25 CCL-124 CEA220M16LS CKSYF104Z25
	C202, C204, C211 C203, C213 Chip Capacitor C205, C217 C206 — C210 Chip Capacitor C212, C221 Chip Capacitor	CEA010M50LS2 CCSSL101K50 CEA10M25LS CKSYB223K25 CKSYB103K50
	C214 C215, C230 C216 Chip Capacitor C218 C219, C220	CEA2R2M50LS2 CEA220M16LS CKSYB681K50 CEA4R7M35NPLL CEA470M16LS
	C222 — C224 Chip Capacitor C225 C226 C227 C228	CKSYB822K50 CQMA183J50L CSZA010M25 CSZA1R5M25 CSZA2R2M25

Mark	Symbol & Description	Part No.
	C229 C231, C232 C251, C254, C257, C274, C277, C286 Chip Capacitor C252, C288 Chip Capacitor	CQSA102J50 CEA3R3M50LS CKSYB223K25 CKSYB103K50
	C253 Chip Capacitor C255, C256, C261, C262, C264 Chip Capacitor C258, C273, C289 Chip Capacitor C259	CKSYB332K50 CKSYF473Z50 CKSYF104Z25 CEA221M10L2
	C265, C282 C266 Chip Capacitor C267 C270 C278, C280, C287 Chip Capacitor	CEA470M16LS CCSPH470J50 CQPA431G100 CCDCH110J50L CKSYF473Z50
	C279 C281 C283 C284 C285	CEA010M50LS2 CEAR47M50LS2 CEA220M16LS CEA3R3M50LS CEAR33M50LS2
	C290 C291, C292 C302, C317, C318 Chip Capacitor C303 Chip Capacitor C304 Chip Capacitor	CEA101M10L2 CCSSH100D50 CKSYF473Z50 CCSCH270J50 CCSCH220J50
	C307, C308 C309, C314, C315 Chip Capacitor C310, C311 C312 C313	CSZA100M25, CKSYB103K50 CEA220M16LS CEA4R7M35LS CEA221M16L2
	C316	CEA221M6R3L2

Miscellaneous Parts List

Mark	Symbol & Description	Part No.
	Graphic EQ. Unit	CWG-127
★	D1, D2	SM-1A-02
★★	M Motor	CXM-104
★	S01 Solenoid	CXP-035
★	S02 Solenoid	CXP-034
★★	S1 Switch (FF/REW)	CSN-070
	C1	CEA471M16L2

11. CABINET EXPLODED VIEW



• Parts List

NOTE:

- For your P
- ★ ★ and
- ★ ★: GEI
- This classit
- number, te
- Parts whos

Mark	No.
	1.
	2.
★	3.
	4.
★ ★	5.
	6.
	7.
	8.
	9.
	10.
	11.
	12.
★	13.
	14.
	15.
	16.
	17.
	18.
★	19.
★	20.
	21.
	22.
	23.
	24.
	25.
	26.
	27.
	28.

Fig. 18


• Parts List

NOTE:

- For your Parts Stock Control, the fast moving items are indicated with the marks ★ ★ and ★.
- ★ ★: **GENERALLY MOVES FASTER THAN ★.**
- This classification shall be adjusted by each distributor because it depends on model number, temperature, humidity, etc.
- Parts whose parts numbers are omitted are subject to being not supplied.

Mark	No.	Part No.	Description	Mark	No.	Part No.	Description
	1.	CDE-859	Cord			CWM-211	Tuner Amp Assy (KEH-9300)
	2.	CNK-095	Case			CWM-210	Tuner Amp Assy (KEH-9000)
★	3.	CAC-770	Button	29.		CBA-106	Screw
	4.	CNN-134	Spacer	30.		BMZ23P025FMC	Screw
★ ★	5.	CSG-176	Switch	31.		CNL-278	P.C. Board
	6.	CNL-562	P.C. Board	32.		YE15FUC	Washer
	7.	CNK-094	Case	33.		CBH-680	Spring
	8.	BMZ26P050FBK	Screw	34.			Arm
	9.	CDF-055	Connector	★ ★	35.	CSF-014	Switch
	10.	CNG-240	Holder	36.			Cover
	11.	CXD-120	Door	37.		BMZ20P040FMC	Screw
	12.		P.C. Board	38.		CSN-071	Switch
★	13.	BG4524K	LED	39.		CXC-743	Bracket Unit
	14.		Lens	40.		CDF-588	Connector
	15.		Door	41.			Bracket
	16.	CBH-684	Spring	42.			Spacer
	17.	CBL-217	Spring	43.		CXK-310	Cassette Mechanism Assy
	18.	BMZ26P040FMC	Screw	★	44.	CAC-554	Button
★	19.	CAA-501	Knob	45.		BMZ30P050FMC	Screw
★	20.	CAA-502	Knob	46.			Bracket
	21.	CXD-119	Grille Assy (KEH-9300SDK)	47.			Bracket
		CXD-166	Grille Assy (KEH-9300, 9000)	48.			Bracket
	22.	BMZ30P060FMC	Screw	49.			Bracket
	23.	BMZ30P040FMC	Screw (KEH-9300SDK)				
	24.	BMZ30P040FMC	Screw				
	25.	CXD-125	Case Unit (KEH-9300SDK)				
		CXD-124	Case Unit (KEH-9300, 9000)				
	26.	PMS26P040FMC	Screw				
	27.	CKS-275	Plug				
	28.	CWM-209	Tuner Amp Assy (KEH-9300SDK)				

12. TUNER AMP ASSY (1/2) EXPLODED VIEW






Fig. 19

• Parts List

Mark	No.	Part No.	Description	Mark	No.	Part No.	Description
	1.	BMZ26P060FMC	Screw		29.	CNW-655	Plate
	2.	CWS-192	Key Board Unit (KEH-9300SDK)		30.	FTD-6082H	LCD (KEH-9300SDK, 9300)
		CWS-197	Key Board Unit (KEH-9300)			FTD-6081H	LCD (KEH-9000)
		CWS-194	Key Board Unit (KEH-9000)		31.	CNG-095	Holder
★	3.	CAC-789	Button (KEH-9300SDK)		32.	CNN-052	Insulator
	4.	CNW-653	Holder		33.	CNW-650	Holder
★	5.	CAC-699	Button		34.	CNW-648	Rubber
★	6.	CAC-700	Button	★	35.	CAC-790	Button
★ ★	7.	CEL-147	Lamp, 14V 40mA		36.	CXD-123	Heat Sink Unit
★	8.	CAC-782	Button		37.	BMZ26P100FMC	Screw
	9.	CAC-783	Button		38.	CKS-272	Plug
★	10.	CAC-784	Button	★ ★	39.	CCS-362	Volume/Switch
★	11.	CAC-697	Button		40.	CBE-084	Spacer
★	12.	CAC-785	Button		41.		Frame
★	13.	CAC-786	Button		42.		Spacer
	14.	CAC-787	Button		43.	CAA-503	Knob
★	15.	CAC-698	Button	★	44.	CCL-123	Feed through Capacitor
	16.	CNL-475	P.C. Board		45.	CNG-088	Holder
	17.	CNL-476	P.C. Board		46.		Holder
★	18.	BG5724K	LED		47.	BMZ30P060FMC	Screw
	19.	BTN26P060FMC	Screw		48.	BMZ30P040FMC	Screw
	20.	CNW-549	Spacer		49.		Insulator
★	21.	BG3422K	LED		50.	CWG-127	Graphic EQ. Unit
	22.	CNW-662	Spacer		51.	CDF-592	Cord
	23.	CNW-549	Spacer		52.		Chassis Unit
	24.	AA3422K	LED				
	25.	CNN-137	Spacer				
	26.	CNN-649	Rubber				
	27.	CNN-754	Lens				
	28.	CNN-656	Rubber				

13. TUNER AMP ASSY (2/2) EXPLODED VIEW

• Parts List

Mark	No.	Part No.	Description	Mark	No.	Part No.	Description
	1.	CDF-731	Connector		21.	CWB-151	FM Front End
	2.	CDF-671	Connector		22.	CDF-660	Connector
	3.	CDF-729	Cord		23.		Insulator
★ ★	4.	CSH-070	Switch		24.	BMZ30P040FMC	Screw (KEH-9300SDK)
	5.	CKS-214	Plug		25.	CNF-387	Clamper
	6.	CKS-271	Plug		26.		Chassis Unit
	7.	CKS-269	Plug		27.	BMZ30P040FMC	Screw (KEH-9300, 9000)
	8.	CDF-590	Connector		28.		Holder (KEH-9300, 9000)
★	9.	CXD-128	Button Unit		29.		Holder (KEH-9300SDK)
★	10.	CXD-126	Button Unit		30.	CDF-668	Connector
	11.	CDF-586	Connector		31.	CDF-591	Connector (KEH-9300SDK)
	12.		Holder		32.	CDF-730	Cord
	13.	CCL-124	Feed through Capacitor		33.	CDH-073	Antenna Cable
	14.		Holder		34.	CDF-706	Cord (KEH-9300)
	15.	CKS-270	Plug				
	16.	BMZ30P040FMC	Screw				
★ ★	17.	CSG-207	Switch				
	18.	CBL-211	Spring				
	19.	BMZ26P030FMC	Screw				
	20.		Holder				

• Tuner Amp Assy (2/2)




Fig. 20

14. PACKING MEHTOD




Fig. 21

• Parts List

Mark	No.	Part No.	Description
	1.	CRD-398	Owner's Manual (KEH-9300SDK)
		CRD-397	Owner's Manual (KEH-9300)
		CRD-396	Owner's Manual (KEH-9300)
		CRD-399	Owner's Manual (KEH-9000)
			Card (KEH-9300SDK, 9300)
			Card (KEH-9300SDK)
			Card (KEH-9300SDK)
	2.	CEA-885	Accessory Assy
	2-1.	CDE-437	Cord
	2-2.	CNF-111	Strap
	2-3.	CNF-382	Lever
	2-4.	CNW-642	Holder
	2-5.		Screw Kit
	2-5-1.	CBA-028	Screw for Strap
	2-5-2.	NF40FMC	Nut
	2-5-3.	NF50FMC	Nut
	2-5-4.	PMB50Y160FMC	Screw

Mark	No.	Part No.	Description
	2-5-5.	WS40FMC	Washer
	3.	CEA-862	Remote Switch Assy
	3-1.		Remote Switch
	3-2.	CWM-684	Spacer
	4.	CHD-333	Styrofoam (KEH-9300SDK)
		CHD-131	Styrofoam (KEH-9300, 9000)
	5.		Cover
	6.	CHD-332	Styrofoam (KEH-9300SDK)
		CHD-130	Styrofoam (KEH-9300, 9000)
	7.	CNF-383	Holder
	8.	CHD-336	Carton (KEH-9300SDK)
		CHD-334	Carton (KEH-9300)
		CHD-338	Carton (KEH-9000)